



4x4 EFI SERIES

VOLUNTEER™ UTILITY VEHICLES

FEATURES

747cc V-TWIN
OHV EFI ENGINE

COLOR OPTIONS:
YELLOW, CAMO,
RED OR GREEN

47.7 FT.-LBS. OF
TORQUE @ 2,400 RPM

TOP SPEED OF 25 MPH

3" LADDER-STYLE
STEEL FRAME

1-YEAR LIMITED
WARRANTY†

14.4 CUBIC FOOT
STEEL BED

ADJUSTABLE
COIL-OVER SHOCKS

†See specifications for warranty information.
‡Includes operator, passenger and bed capacity.

POWERFUL UTILITY. EXTREME VERSATILITY.

No matter what the job demands, the Volunteer series of 4x4 EFI utility vehicles delivers. With its on-demand 4x4 system you get four-wheel drive performance at the flick of a switch. And with dual A-arm, independent suspension and adjustable coil-over shocks, no matter where you're headed, you'll be traveling in comfort.

INDUSTRY-LEADING FEATURES. THAT'S THE STRENGTH OF THE **CUB CADET ADVANTAGE.**



UNRIVALED VERSATILITY

With more than 40 available attachments, no task or adventure will hold you back. It's designed to do it all while letting you enjoy the outdoors.

HAUL THE HEAVIEST LOADS

With a 1,400-lb payload capacity,‡ even large jobs are no match. The Volunteer takes it with ease, meaning fewer trips for you to get the job done faster.



READY FOR ANYTHING

The Volunteer 4x4 EFI is ready for any job. On campus, at work, or in the yard, finish what needs to get done while having some fun.



Cub Cadet®

YOUR INDEPENDENT DEALER — EXPERT SERVICE. LOCALLY OWNED.
THE ADVICE, SELECTION AND SUPPORT YOU NEED TO FIND THE RIGHT FIT
IS AT YOUR LOCAL CUB CADET DEALER.

OPTIONAL EQUIPMENT FOR ALL VOLUNTEER™ UTILITY VEHICLES



ACRYLIC WINDSHIELD (A200)

Mounts directly to OPS to protect operator and passenger from the elements.



SOFT ROOF AND REAR WINDOW (A201/B201)

The Cub Cadet soft roof is made from weather-resistant, UV-coated nylon for durable protection.



LIGHT BAR (A70022)

Low-profile light bar has four 35-watt adjustable driving lights for added visibility.



WARN® 4,000-LB. WINCH AND MOUNTING PLATES (A70015)

4,000-lb. winch with remote control and steel cable.



HOOD RACK (A206)

Steel hood rack with headlight guards provides extra storage.



72" SUPER-DUTY SNOW BLADE WITH MANUAL ANGLE (A70024)

Angles up to 28 degrees with heavy-duty skid shoes and four adjustable springs. Not compatible with winches. Winch not required.



14" ALUMINUM RIMS AND 26" OFF-ROAD TIRES (B235)

Set of four 14" aluminum rims and 26" heavy-duty, radial Goodyear MTR tires.



BENCH SEAT (A70003)

Comfortably fits two people for maximum efficiency.



COMPLETE DELUXE CAB (A70025-A70028)

The contoured design and thick poly reduce noise levels and provide maximum coverage for both the driver and passenger.

ENGINE

4x4 EFI

Engine	31 HP* Kohler® Aegis® V-Twin EFI
Displacement	747cc
Fuel	Gas
Torque	47.7 ft.-lbs. at 2,400 rpm
Ignition	Transistor controlled
Lubrication	Full pressure w/ spin-on oil filter
Engine Cooling	Liquid
Air Cleaner	Heavy-duty, replaceable

SUSPENSION

Shocks	Adjustable coil-over
Travel	8"

FRAME

Frame	3" ladder construction
Receiver	2" – class 1
Bumper	Steel

TRANSMISSION

Drive	Enclosed CVT
Front Differential	Hilliard® front differential
Rear Differential	Mechanical differential
Speed	0 – 25 mph
Transaxle	Fully enclosed, oil bath
Selector	Hurst® shifter (H-L-N-R)
Rear Axle Housing	Cast-iron

ELECTRICAL SYSTEM

Battery	450 cold crank amp
Alternator	12V – 65 amp
Headlights	Halogen 37.5 watts
Wiring	Automotive fused
Power Port	12V in-dash

CONTROLS

Brakes	4-wheel, 8" hydraulic disc
Brake Lines	Stainless steel braided
Parking Brake	Mechanical
Steering	Rack and pinion
Indicators	Fuel, battery, oil, parking brake and hour meter

CAPACITY

Towing/Payload	1,400 lbs. (total payload includes operator, passenger and bed capacity)
Fuel Tank	6 gal.
Cargo Box	Steel (1,000 lbs.) L/W/H: 51.6"/42"/11.5"
Storage	Glove box, under-seat

SEATS

Seats	Sport
-------	-------

TIRES

Tires	Trail
Front Tire Size	26" x 9" – 12"
Rear Tire Size	26" x 11" – 12"
Rims	12" steel

DIMENSIONS

Length/Width/Height	119"/63.55"/73"
Tread Center	F: 52"/R: 50"
Wheelbase	78"
Ground Clearance	11" (under foot platform)
Turning Circle (diameter)	22'
Weight	1,650 lbs.

WARRANTY*

	1-year limited residential
--	----------------------------

Cub Cadet Utility Vehicles are intended for off-road use by adults only. They are neither designed nor equipped to be registered as motor vehicles for use on public roadways. Always use extreme caution when operating utility vehicles, and carefully follow all operating, maintenance and safety instructions and warnings. Please see the operator's manual and the warning labels posted on the vehicle itself for more details.

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

*As rated by Kohler, all power levels are rated at 3600 RPM per SAE J1940 gross † See your local Cub Cadet Independent Dealer for warranty details.
773-05776 Printed in U.S.A. 12/14 © 2015 Cub Cadet

